

Panel PC For Kiosk & Digital Signage

AGMATEL Panel Pcs are revolutionizing the traditional bulky Kiosks with ultra slim, advanced and exquisite metal enclosure catches most eye contacts. Panel PC includes three different display sizes 15", 17" and 19" equipped with high brightness TFT panel and SAW touch. IP 55 dust and water proof display front industrial application requirements.

Panel PC is an excellent choice for digital signage, information kiosk, healthcare, industrial automation and other application.



Features




60mm

1. Ultra Slim, 60mm thickness



2. Rugged metal housing and IP 55 dust & water proof display front



3. Intel mobile technology supports multiple processors from Fanless ULV CPU to High performance Pentium M CPU



4. Rich I/O ports provide excellent peripheral connectivity.



5. 15", 17" & 19" wide range display size.



6. Slim HDDbay design for easy service.

Panel PC For Kiosk & Digital Signage



Specifications

Model Name	Panel PC 15	Panel PC 17	Panel PC 19
Motherboard			
CPU	Intel Pentium M 1.8 GHz		
Chipset	Intel 852GM/855GME and ICH 4 FSB 400MHz		
System Memory	2 x DDR SO-DIMM Slot Up to 2 GB		
Graphic Memory	System Memory Shared up to 96 MB		
BIOS	AWARD BIOS		
LCD Touch Panel			
LCD Size	15" TFT LCD	17" TFT LCD	19" TFT LCD
Brightness	300 Cd/m ²	350 Cd/m ²	350 Cd/m ²
Maximal Resolution	1024 x 768	1280 x 1024	1280 x 1024
Touch Screen Type	Intelligent SAW touch		
Storage			
HDD	2.5" Slim HDD 40 GB		
ODD	Optional Compact Flash memory (without HDD)		
Expansion			
External I/O			
PS /2 Keyboard	1		
USB	4 Ports (V2.0)		
Serial / COM	4xRJ-45 (COM1 standard RS-232, COM2 RS-232/422/485 selectable by jumper; COM3&COM4 pin 9 with 5V or 12V power by jumper)		
Parallel	1x D-sub 25-pin connector		
LAN (10/100)	1xRJ - 45		
Cash Drawer	1XRJ-11 (12V or 24V)		
DC Jack	1XDC Jack latch type		
Audio Jack	1X Line-out, 1 x Line -in		
2nd GA	DB15-pin connector		
Internal Interface			
USB	2		
Audio	Internal Speakers		
Speaker	2x3 Watt speakers		
Environment			
Operating Temperature	0°C - 40°C,		
Storage Temperature	-20°C - 60°C,		
Operating Humidity	5% - 95% RH non-condensing		
Storage Humidity	5% - 95% RH non-condensing		
Dust and water Proof	Ip55 Compliant		
Dimension (WxDxH)	368 x 293 x 60 mm	410.5 x 344.5 x 60 mm	449.2 x 374.2 x 60 mm
Weight (Net wt/Gross wt)	5.8 Kgs/6.8 Kgs	7.6 Kgs/8.6 Kgs	9 Kgs/10 Kgs
Mounting	100 mm x 100m Standard VESA mounting holes		
OS Support	Windows XP Embedded / XPP / VISTA / Linux		

Head Office

E-366, IInd Floor, Nirman Vihar, Vikas Marg, Delhi-110092
 Ph: 011-22010555-777-999, 22462256 22456529 Fax : 011-22019833
 E-mail: itsales@agmatel.com

Branches :
 Delhi - 9313631201, 9313631207, Chandigarh - 9855640717, Lucknow - 9335497024, Dehradun - 9897002860, Jammu - 9419134112, Bhopal - 9826248587, 9826248587, 0755-6451876, Jaipur - 09990184491,
 Maharashtra & Gujarat- 09313631205, Nagpur - 9975414998, Raipur - 9425502784, Bangalore - 9342139297, 9844022033, Hyderabad - 391225696, Kolkata-9836180361, 033-22900865, Guwahati-9957193206

Southern Regional Office

158-35/3, IIInd Main Road, Industrial Town, Rajaji Nagar,
 Bangalore-560044 (Karnataka) Ph: 09844022033 Fax : 080-23424889
 Email: arvind@agmatel.com